




**SPECIFICATION:**

JOSAM 12674-58-6 SERIES COATED CAST IRON LONG BARREL LEFT-HAND HORIZONTAL 4" NO-HUB FITTING WITH 2" NO-HUB VENT AND ADJUSTABLE CARRIER BODY, ABS EXTENSION WITH INTEGRAL TEST CAP, PYLON FEET, ANCHOR FOOT, PLATED HARDWARE AND NEOPRENE FIXTURE GASKET, INVERTIBLE FACEPLATE FOR SIPHON JET OR BLOWOUT CLOSETS WITH SUPPLY PIPE SUPPORT.

**CLOSET CARRIER  
LEFT HAND**

SERIES **12674-58-6**



△ FOR DIMENSION SHORTER THAN 5-1/2" (1" MIN) CUT EXTENSION FOR LONGER EXTENSION (10-1/2" MAX) SPECIFY (-10)

☒ RECOMMEND FEET BE SECURED TO FLOOR WITH 1/2" BOLTS AND ANCHORS (BY OTHERS)

⊗ FOR SIPHON JET ROUGHING OVER 6" OR BLOWOUT ROUGHING OVER 12-1/2" SPECIFY ON ORDER.

SIPHON JET DIMS SHOWN. FOR BLOWOUT DIMS, USE:

- MIN 2" & MAX 4"
- ▭ MIN 11 & MAX 16-1/2"

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

	-PF	PYLON FOOT, STD.
	-OR	O-RING CARRIER
	-SDH	SPECIAL-DUTY 750 LB. CARRIER
	-HS	HUB & SPIGOT
	-AUX	AUXILIARY INLET
	-VP	VANDAL-PROOF TRIM
	-1	POSITIONING FRAME
X	-6	SUPPLY PIPE SUPPORT (SPECIFY TYPE OF PIPE)

	-10	ABS EXTENSION THROUGH 10-1/2" WALL
	-24	FLOOR MOUNTED BACK OUTLET CHINA BOWL
	-30	CAST IRON ADJ. EXTENSION W/ CONNECTOR
	-30-2	CAST IRON ADJ. EXT. W/ CONNECTOR & TEST CAP
	-32	CARRIER FOR WIDE CHASE INSTALLATIONS
	-35	CARRIER FOR WHEELCHAIR HIGH ROUGH
X	-58	LONG BARREL FITTING
	-XSD	EXTRA SPECIAL DUTY 1,000 LB CAPACITY

DATE OF LAST CHANGE: 11/14/22 JTJ

DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCES AND CHANGE WITHOUT NOTICE. WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA.

**JOSAM**  
MICHIGAN CITY, INDIANA

NOTES